
#### JMCG Facts

The only commercial vehicle company establishing joint-ventures with 3 of Fortune Global 500 enterprises in China (Ford, Isuzu, Renault) Over 5 decades of experience in manufacturing vehicles



Jiangxi Jiangling Motors Import & Export Co., Ltd.
Add: 969, Jinrong Street, Honggutan District, Nanchang, Jiangxi, China
Tel: +86-791-86738769 Fax: +86-791-86738577
Website: www.jmcg-global.com



No.1 No.1 Top 2 Top 5
Light bus share Ambulance share Pickup share Light truck share


JV with Ford f JMCGMotors

### POWERTRAIN



**JX493** 2.8L 4-cylinder


Max. Torque, 330N-m /1400-2500r/min





JX4D30 2.9L 4-cylinder

Max. power 120kW Max. torque 450N-m Torque 350Nm at 1000 rpm Garrett's 4th generation turbocharger HT300 cylinder material with a life expectancy of 700,000 km



JMC

# RIGOROUS TESTING

Leading-edge manufacturing processes to ensure the manufacturing quality of our products

The agile and robust development process and strict verification standards have established the excellent quality standard of JMC light trucks

28 ITEMS Full range of road conditions, including twists, potholes, rocky roads, splash pads and more. Specialised test conditions.







2 times the industry level.



3000 System level test cases





13%









# INTERIOR

#### **ERGONOMIC DESIGN**

- New driver-centric interior hugging dashboard design
   Flat cabin design with improved the inner space
- 17 storage areas for infinite space extension & USB and 12V power interface
- Reversible handbrake providing a flexible inner space
- Standard with power windows
- Ergonomic seats with 5-level adjustment armrest
- Multifunctional steering wheel







Center USF









# LOAD-BEARING

STRAIGHT THROUGH BEAM DESIGN:


Frame section height—180mm

FRONT AXLE:

Made of high-strength alloy steel

For higher strength and load-bearing capacity

**UPGRADE CABIN WIDTH** 





#### **QSTE650TM FRAME:**

The strongest ultra-high strength steel in the industry

#### MODIFICATION FLEXIBILITY:

Standard hole design

More convenient to install special vehicle modification accessories





# **ENERGY CONSERVATION**

2 0.45 air resistance coefficient

∅ 0.0065 rolling resistance tires

### SECURITY









- 1 Hydraulic brake reaches the level of air brake(Air brake optional)
- Wide wheelbase, wide leaf spring distance, Widest 900 mm frame in its class (wide body model)
- 3 4.38° A-pillar obstacle angle for less blind spot, more open view, safer driving

Model					All New Carrying Plus										
Cabin type			C/DC				C/DC			/KC		SC	SC/KC		SC
Emission standard	E2	E4	E5	E6	E2	E4	E5	E6	E2	E4	E5	E6	E4	E5	E6
							Dimension								
Wheelbase(mm)			150							3360					
Cabin width(mm)		18	90			1:	890					2060			
Overall Dimension Cargo body L*W*H(mm)	SC/KC: 5490°2080°2435/2450 DC: 5490°2080°2450/2465				SC: 5990*2080*2425/2435 DC: 5990*2080*2435/2450				5990*2180*2445/2465				5990*2180*2445/2465		
Cargo size L*H(mm)	SC: 3700*440 KC: 3300*440 DC: 2700*440				SC: 4200*440 DC: 3200*440				SC: 4200*440 KC: 3800*44				0		
					Powertrain										
Engine					JX493								JX4D30		
Displacement(cc)					2771								2892		
Max.Output(kw)/Rpm	68/3600 90/3200			68/3600 90/3200			68/3600 90/3200				120/2800				
Max.Torque(Nm)/Rpm	220/1800-2200 330/1600-2200			220/1800-2200 330/1600-2200			220/1800-2200 330/1600-2200				450/1200-2400				
Gearbox Type					5MT								6MT		
Fuel Tank Capacity (L)		66			105				125				125		
Rear axle speed ratio	6.142		5.571		6.142		5.571		6.142		5.571			4.222	
	57.12			_	51.12	_	Brake&Tire	_				_	_		
Brake type				Hydraulic			brukearire	Hydraulic/Air	Hydraulic		Hydraulic/Air			Air	
Tire type		Single Peer Tire	/Dual Rear Tires	Tiyurauic				Tiyuraulic/All	Tiyurauic	Dual Rear Tires	Tiyuraunc/Air			All .	
The type		Jilgle Neal Tile	Dual Real Tiles							Dual Near Tires					
Tire size	Single Rear Tire: 7.0R16 14PR Dual Rear Tire: 7.0R16 10PR			Single Rear Tire: 7.0R16 14PR 205/75 R17.5 Dual Rear Tires: 7.0R16 10PR	7.0R16 10PR			7.0R16 10PR 205/75 R17.5	7.0R16 10PR			7.0R16 10PR 215/75 R17.5	Standard: 7.UR16 10PR		Standard: 7.0R16 10PR 215/75 R17.5 Optional: 7.5R16 16PR
							Weight								
Kerb weight(kg)	Single Rear Tire: 2265/2280/2400 Dual Rear Tires: 2315/2375/2465	Single Rear Tire: 2305/2325/2440 Dual Rear Tires: 2355/2415/2505	Single Rear Tire: 2340/2355/2475 Dual Rear Tires: 2405/2445/2540	Single Rear Tire: 2345/2360/2480 Dual Rear Tires: 2410/2450/2545	2420/2495	2460/2535	2495/2570	Hydraulic brake: 2500/2575 Air Brake: 2600/2675	2515/2545	Hydraulic brake: 2515/2545 Air Brake: 2615/2645	Hydraulic brake: 2550 Air Brake: 2650	Hydraulic brake: 2555 Air Brake: 2655	2695/2785	2730	2735
GVW(kg)		Single Rear Tire: 4495	Dual Rear Tires: 5495			5	495			54	95			5495	
							Safety								
ABS		•	•		•		•	•	•	•		•		•	•
Exhaust Brake		0		0	•	•	•	•	•	•	•	•	•	•	•
Power Steering	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sound alert for handbrake not released	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Reminder of unfastened seat belt for driver	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LED daytime running light	1	,	,	•	,	,	,	•	,	,	1	•	,	,	•
LED dayanie running light	,	,	,	•	,	· · · · · ·	Comfort	•	,	,	,	•	,	,	
							Comfort								
Infotainment System (Bluetooth music / Bluetooth phone / USB music)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Multifunction steering wheel	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Air conditioning	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Central locking(manual)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Remote key	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Power windows	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
One-touch window liftdriver	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Remote key control glass one-touch lift	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Driver armrest	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Headlight delay off	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Driver overhead storage box	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
USB charging port		•	•	•	•	•	•		•	•	•	•	•		•
Overhead storage box mounted USB port	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
12V Socket/ Power Port DC 12V Outlet	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Speed-sensitive automatic door locking	1	•	•	•	,	•	•	•	,	•	•	•	•	•	•
Standard O:Optional /:Not Available		•	•	•	,	•		•	,	•	•	•	•		s subject to change.



...

#### **World-class supplier**



Light Truck: Electronic control unit. sensors, oil pump, fuel injector Pick Up/SUV: Fuel injector, ESP assembly



SUV (Diesel model):

. . . .

. . . .

....



SUV/Pick Up: Transfer box assembly. transfer box ECU



...... ....



ACU (Airbag control unit)



. . . . . .



Light Van (Gasoline model): Clutch, fuel pump plunger SUV (Diesel model): Generator OAP beit pulley



SUV/Pick Up: Electronic gear shifter, automatic transmission.EPS assembly





Light Truck:







Light Van: Clutch



Light Van (Gasoline model):







Light Truck: Pistons and piston rings



Light Truck: Combined instrument, A/C control panels, HVAC, condenser Lighe Van: Combined instrument



SUV/Pick Up: Exhaust pipe system



**GPDS** Ford Global Quality Ford Global Product Improvement Process Development System



- Exported to 110 countries and regions

- UN authorized supplier